THE STATE TRADING CORPORATION OF INDIA LIMITED

(A Government of India Enterprise)
5th Floor, Mogul's Court, Basheerbagh,
Hyderabad 500 001.

Tender for Supply, Delivery, Mounting, Testing and Commissioning of 1 No Turn Table Ladder Platform of 55 Mtr. (working height) equipment

Tender Notice No: STC/HYD/GID/2017-18/07
Dated 07.03.2018

Corrigendum No. 01 Dated 23.03.2018

Corrigendum No 01 Dated 23.03.2018

In the Tender for Supply, Delivery, Mounting, Testing and Commissioning of 1 No Turn Table Ladder Platform of 55 Mtr. (working height) equipment the following Amendments are made.

Section I

Cover #1(Techno-commercial Bid) shall contain the certified copies of following documents.

General Conditions of Contract (GCC)

14. Spare Parts:

| Clause No | Original Clause | Revised Clause |
|-----------|--|------------------------------------|
| 14.1 | Supplier shall maintain sufficient inventories to assure ex-stock supply of consumables spares, accessories, components and other spares and shall ensure delivery of the same as prompt as possible but in any case, within Thirty (30) days of placement of order. | Supplier shall maintain sufficient |

| Clause No | Original Clause | Revised Clause |
|---------------------------|-------------------------------|--------------------------------|
| Section - IV | The price and the cost stated | For Import, Price, Freight |
| Table of Clauses | in the tender shall be in | and Insurance are to be in |
| 10. Payment (Refer Clause | Indian Currency only | USD or any other freely |
| 18 of GCC) | | convertible Currency. The |
| 6. (d) | | charges, expenses etc., to be |
| | | incurred in India are to be in |
| | | INR. |
| General Conditions of | Payment shall be made in | For Import, Price, Freight |
| contract | Indian rupees or in freely | and Insurance are to be in |
| 18. | convertible foreign currency | USD or any other freely |
| II | for imports. In case of local | convertible Currency. The |
| 18.4.1 | supply or certain items are | charges, expenses etc., to be |
| | locally supplied for an | incurred in India are to be in |
| | otherwise imported item, the | INR. |
| | same shall be quoted in INR | |
| | and the payment for same | |
| | shall be made in INR only. | |

14. Documents Establishing Goods Eligibility and conformity to bidding documents.

| Clause No | Original Clause | Revised Clause |
|-----------|--------------------------------------|--------------------------------------|
| 14.2 | The documentary evidence of the | The documentary evidence of the |
| | goods and services eligibility shall | goods and services eligibility shall |
| | consist of statement in the price | consist of the conformity, clause |
| | schedule on the country of origin | wise/technical specification |
| | of the goods and services offered | compliance is a part of technical |
| | which shall be confirmed by a | bid and needs to be uploaded as |
| | certificate of origin at the time of | such |
| | shipment | |

General Conditions of Contract (GCC)

17. Inspection

| Clause No | Original Clause | Revised Clause |
|-----------|---|--|
| 17 | The successful bidder shall have the work inspected and approved at the following stages by the Director General of Fire and Emergency Services or his authorized representative. a) Chassis inspection prior to collection from dealer b) Visual inspection and testing and working of all the tools and equipment, Paint finishing and logo writing. c) Final Inspection and Road test of the Vehicle. | May please be referred to point no: 8.2 in General Conditions of Contract (Page No: 20) in the Tender Document |
| | from dealer b) Visual inspection and testing and working of all the tools and equipment, Paint finishing and logo writing. c) Final Inspection and Road test of the | |

18. Payment:

| Clause No | Original Clause | Revised Clause |
|--|---|--|
| 18.3.1 I. For Imported Item iii) | Certificate of satisfactory Pre- dispatch inspection report and Supplier factory inspection report. | May please be referred to point no: 8.2 in General Conditions of Contract (Page No: 20) in the Tender Document |
| 18.4.3 | Acceptance/Clearance: The final acceptance of the quality and quantity of the goods dispatched shall be at the final place of destination in India after inspection of the goods by the end-user or its nominee. Supplier will be liable to accept without contest claims filed by the enduser or the STC regarding short supply/defective/substandard quality of goods if any as found | May please be referred to point no: 8.2 in General Conditions of Contract (Page No: 20) in the Tender Document |

| on arrival in India or after | |
|--------------------------------------|--|
| inspection at the final destination | |
| on the basis of certificate from the | |
| end-user department/STC to | |
| support the claim. The supplier to | |
| inform the list of installation pre- | |
| requisites immediately on receipt | |
| of order. | |

Annexure VIII & IX

| | | Clarification |
|---------------|-------------------------|------------------------------------|
| Annexure VIII | Schedule of Tools | Only the Quantity/Unit shall be |
| | | quoted. However, in Price Bid cost |
| | | of all accessories to be included. |
| Annexure IX | Schedule of Spare Parts | Only the Quantity/Unit shall be |
| | | quoted. However, in Price Bid cost |
| | | of all accessories to be included. |

Annexure IX

1.12 Cage

| Clause No | Original Clause | Revised Clause |
|-----------|--|--|
| | Original Clause | |
| 1.12.1 | The working cage shall be attached | The working cage shall be attached |
| | to the tip of top section and it shall | to the tip of top section and it shall |
| | be foldable. Additionally, the cage | be foldable. Additionally, the cage |
| | shall also be Fixed/Detachable | shall also be Fixed/Detachable |
| | Type The vehicle should be always | Type The vehicle should be always |
| | in ready to go situation. There shall | in ready to go situation. There shall |
| | be sufficient space of at least 1 | be sufficient space of at least 1 sq.m |
| | sq.m of standing area for three | of standing area for three persons |
| | persons and safe working load | and safe working load shall not be |
| | shall not be less than 270 kg | less than 270 kg excluding the |
| | excluding the equipment | equipment permanently mounted in |
| | permanently mounted in the cage. | the cage. The working cage shall be |
| | The working cage shall be kept 1 1 | kept 1 1 horizontally leveled in any |
| | horizontally leveled in any | position of the booms. The leveling |
| | position of the booms. The | system shall be controlled by an |
| | leveling system shall be controlled | automatic horizontal level |
| | by an automatic horizontal level | monitoring device with two fully |
| | monitoring device with two fully | automatic and independent safety |
| | automatic and independent safety | circuits in case of an uncontrolled |
| | circuits in case of an uncontrolled | leveling failure. Manual emergency |
| | leveling failure. Manual | control of the cage leveling system |
| | emergency control of the cage | to be provided either from the |
| | leveling system to be provided | master control position or cage |
| | from the master control position as | itself |
| | well as cage itself | |

| 1.12.7 | An emergency cage leveling operation shall be provided in case of failure near the main operator's seat | Manual emergency control of the cage leveling system to be provided either from the master control position or cage itself. |
|--------|---|--|
| 1.12.9 | The working cage control panel incorporating all control levers and safety system indications shall be fitted in the left side corner of the rescue cage and shall be moveable to the left front of the cage. A centre position shall not be allowed, ensuring easy access from the centre front access to the rear ladder access door. The Joy stick in the cage shall be identical that of the main console. The cage control panel shall always be visible and accessible, even when the additional equipment is used by the fireman. Two xenon flood lights shall be provided in front of the cage for illumination during night operations | The working cage control panel incorporating all control levers and safety system indications shall be fitted in the left side/centre position of the rescue cage. All other accessories and conditions of the original clause to be complied with. |